

# L-STAY BERM INSTRUCTIONS

L-Stay Berms offer simple, reliable secondary containment. Their 6061 aircraft-quality aluminum stays hold the walls in place, yet are easy to remove and reinstall when you need to drive in or out. We build our berms out of durable, chemical resistant fabric that you can depend on.

## WHAT YOU NEED TO KNOW

### SITE PREP

1. Clear a deployment area of debris that might damage the berm.

### DEPLOYMENT

1. Unfold the berm.
2. Insert the L-Stays into the wall pockets.
3. Lift the berm walls.
4. Slide the staking patches onto the L-Stays *(if needed)*.
5. Drive stakes through the grommets in the staking patches (Stakes Not Included).

### REPAIR

1. Clean the area to be patched using denatured alcohol.

**Note:** Patches should always be applied to the inside of the berm.

2. Cut out the patch material, rounding the corners so that they don't peel up.
3. Peel the paper backing from the adhesive patch.
4. Center the patch over the hole.
5. Apply the patch in a rolling motion.
6. Rub out any bubbles.



### AFTER USE

1. Drain the berm according to environmental regulations.
2. Remove the L-Stays.
3. Fold the berm.
4. Store in a dry place, protected from the sun and rodents.

## RECOMMENDED PRODUCTS



Mini Spill Kit



Diversion Tube



Spill Monkey Filter

Need a custom size, color or design? Call 1 (800) 247-3846.

