

QUICK SNAP FOAM BERM DATA SHEET

Even with efficient designs, dropping a berm wall takes time. Multiply that time by the number of times your operators are going to drive in and out of fueling and check stations. You'll quickly see that this berm is worth the extra money. The Quick Snap Foam berm has thick non-memory foam ends that crush momentarily and then regain their shape when driven over, even by heavy equipment.

WHAT YOU NEED TO KNOW

- Quick and easy set up, no tools necessary
- Designed for high traffic secondary containment
- 30 oz. chemical and UV resistant material
- Thermal welded 1.5" seams
- Ground stake compatible for windy conditions
- Contains environmental hazards ie: Fuel, oil and fracking chemicals
- EPA, OSHA, NPDES compliant. Meets 40 CFR 112.7, 40 CFR 122.26, 40 CFR 264.175
- Standard 1 year warranty
- Proudly made in the USA



SPECIFICATIONS

	Internal Width ft.	Internal Length ft.	Wall Height in.	Weight lbs.	Sump gal.	Containment Area sq. ft.	Set Up Dimension ft.	Stake Down Points	Material oz. ASTM D751	Low Temp. ASTM D2136 F	High Temp. ASTM D471 F	Puncture lbf. ASTM D4833	UNSPSC
12x26x12	12	26	12	185	2333.9	312	14x28	10	30	-30	180	248	24111812
12x36x12	12	36	12	200	3231.5	432	14x38	12	30	-30	180	248	24111812
12x50x12	12	50	12	300	4488.3	600	14x52	14	30	-30	180	248	24111812
12x60x12	12	60	12	325	5385.9	720	14x62	16	30	-30	180	248	24111812
14x54x12	14	54	12	481	5655.2	756	16x56	16	30	-30	180	248	24111812

RECOMMENDED PRODUCTS

DIVERSION TUBE



GOGO BERM



WATER BLADDER



Need a custom size, color or design? Call 1 (800) 247-3846.

